

# Portal Light 2



## Technical Specifications

# Portal Light 2

<b>Physical</b>	<b>Height</b> <b>Width</b> <b>Depth</b> <b>Visual status indicator</b> <b>Product identification</b>	3.2 in (82 mm) 2.0 in (51 mm) 1.1 in. (30 mm) RGB LED MAC address, Unique ID
<b>Environmental</b>	<b>Operating temperature</b> <b>Storage temperature</b> <b>Operating humidity</b> <b>Storage humidity</b> <b>IP protection</b>	14°F to 149°F (10°C to 65°C) -4°F to 185°F (-20°C to 85°C) 0%-95% RH (non-condensing) 5%-95% RH (non-condensing) IP 52
<b>Bluetooth Low Energy Radio</b>	<b>Wireless standard</b> <b>Range</b> <b>Output power</b> <b>Frequency range</b>	Bluetooth LE 5.0 and 5.3 compatible Up to 98 feet (30 meters) 8 dBm 2.402GHz -2.480GHz
<b>Electrical power</b>	<b>Plug type</b> <b>Input voltage</b>  <b>Output voltage</b> <b>Output power</b>	Type B (North American 3-pin-plug) 110 VAC ~100-270VAC, 20A rated for pass-thru (accepted range 100V-240VAC) 3.3 VDC 2W
<b>Wi-Fi radio</b>	<b>Wireless networking</b> <b>Frequency range</b> <b>Security</b> <b>Wireless authentication</b> <b>Network communication</b> <b>IP addressing</b> <b>Data packet size</b>	IEEE 802.11 a/b/g/n 2.4GHz and 5GHz WEP, WPA™/ WPA2™ PSK, WPA2 Enterprise, WPA3™ Personal EAP-TTLS (MSCHAPv2), PEAP v0 (MSCHAPv2) Hypertext Transfer Protocol Secure (HTTPS)/TLS 1.2 Dynamic Host Configuration Protocol (DHCP) Typically less than 6 kilobytes (kB) per second
<b>Features</b>	Bluetooth Low Energy (LE) broadcasting and scanning Remote device management Over-the-air (OTA) firmware and configuration updates Pass-through outlet	
<b>Certification</b>	FCC/UL - Pending types	



# Get in Touch

## **Kontakt.io**

Stoczniewców 3, 30-709  
Kraków, Poland

T +48 123 793 445

E [hello@kontakt.io](mailto:hello@kontakt.io)

## **Kontakt.io**

19 W 34 Street, Suite 1018,  
New York Zip 10001

T +1 415-295-4558

E [hello@kontakt.io](mailto:hello@kontakt.io)