

Temp Monitor Pro



Technical Specifications

Temp Monitor Pro

Physical	Height Width Depth Weight Casing IP rating Visual status indicator Audio alarm Product Identifier Display Control buttons Inputs Mounting	3.9 in (100 mm) 3.9 in (100 mm) 1.1 in (30 mm) 7.7 oz (219 grams) IP54 LED (green, yellow, red) Yes QR code, MAC address, Unique ID 2.1 in (53.3 mm) diagonal Color MIP-LCD Shows status, last reading, low/high thresholds, min/max Three tactile push-buttons below display Two probe ports (Probe 1 & Probe 2); USB-C with integrated screw-lock Built-in magnet; external mounting plate included
Operation	Local device alarm Alarm delay (configurable) Sampling interval Logging Interval (configurable) Local stored reading capacity	Audio and visual; out-of-range reading, probe disconnected, low battery, hardware error 0 to 60 minutes 1 minute 1 to 60 minutes 30 days with 15 min logging interval; max. 10080 stored samples
Environmental	Operating temperature Storage temperature Operating humidity Storage humidity Storage shelf life	-4°F to +158°F (-20°C to +70°C) Recommended: ≤ +86°F (≤ +30°C) 5%-95% RH (non-condensing) 10%-95% RH (non-condensing) 2 years
Battery Power	Battery life Battery type Number of batteries Total capacity Replaceable Power activation	Up to 3 years; factory default configuration ERI4505; 3.6V AA 3 7200 mAh Yes Button press; long press (5s) to power on. Power off disabled by default
Bluetooth Low Energy (LE)	Wireless standard Range Receiver sensitivity Available transmission power level Supported data packets	Bluetooth LE 5.0 Up to 98 feet (30 meters) in open space -96dBm -20 to +4 dBm Kontakt.io Telemetry and Location, iBeacon, Eddystone
Sensors and Peripherals	Ambient Temperature sensor Relative Humidity sensor Kontakt.io Probe NIST Kontakt.io Probe Standard	Range: -30°C to +70°C (-22°F to +158°F) Accuracy: ±1°C (±1.8°F) overall; ±0.5°C (±0.9°F) from -22° C to +50°C (-7.6°F to 122°F) Range: 0 to 95% Accuracy: ± 2% typical, ± 4% max Range: -50°C to +150°C (-58°F to 302°F) Accuracy: ±0.5°C (±0.9°F) Range: -50°C to +150°C (-58°F to 302°F) Accuracy: ±0.5°C (±0.9°F)
Certifications	CE, FCC Part 15B, RoHS, REACH	Optional NIST certification available at time of order placement

Technical Specifications

Temp Monitor Pro

Features

- Continuous temperature monitoring for refrigerators, freezers, and warmers
- 3 year NIST certification available
- Two temperature probe inputs for Kontakt.io probes
- Ambient temperature and humidity monitoring
- Local reading storage up to 30 days
- Local audio and visual alarms
- Over-the-air (OTA) firmware and configuration

Configurable parameters

Bluetooth LE parameters

Parameter	Factory default*	Configurable
BLE packets	Kontakt.io Telemetry, Location	Yes; Kontakt.io Telemetry, Location, iBeacon, Eddystone
BLE interval	1000 ms	Yes
BLE name	Kontakt	Yes
iBeacon major, minor, UUID	Random	Yes; custom request
TX power	-4 dBm	-20 to +4 dBm

Button and sensor parameters

Parameter	Factory default*	Configurable
Turn off with long button press	Disabled	Yes; disable/enable
Ambient Temperature sensor	On	No
Humidity sensor	On	No

*Custom or use-case configuration can be requested at the time of order placement.

 **kontakt.io**

Get in Touch

Kontakt.io

Stoczniewców 3, 30-709
Kraków, Poland

T +48 123 793 445

E hello@kontakt.io

Kontakt.io

133 West 19th Street 7th Floor
New York, NY 10011

T +1 415-295-4558

E hello@kontakt.io